


PB - CPB Series Feed Through and Earth Terminals

CPB 6

Width: 9,50 mm



42,80

CPB 6 B


Width: 13 mm



44,60

CPB 6 U

Width: 13 mm



42,60

Cat No:

326 809
326 800

Cat No:

326 819
326 810

Cat No:

326 829



Electrical Ratings
CE (EN 60947-7-1 / EN 60947-7-2)
UL
VDE (IEC 60947-7-1)
CSA
ATEX

Voltage, V ~	Current, A	Cross-Section
800	41	6 mm ²

Voltage, V ~	Current, A	Cross-Section
800	57	10 mm ²

Voltage, V ~	Current, A	Cross-Section
500	57	10 mm ²

Connection Data
Conductor cross section solid (min.-max.)
Conductor cross section stranded (min.-max.)
AWG Conductor
Torque (min.-max.)
Bolt Diameter
Screwdriver

0,5-6 mm ²
0,5-6 mm ²
AWG 20-10
0,8-1,2 Nm
3,5 mm
IKTD 4 (0,8x4,0)

0,5-10 mm ²
0,5-10 mm ²
AWG 20-8
1,2-1,8 Nm
4 mm
IKTD 4 (0,8x4,0)

0,5-10 mm ²
0,5-10 mm ²
AWG 20-8
1,2-1,8 Nm
4 mm
IKTD 4 (0,8x4,0)

End Plate - Disconnect Plate

Type	Order No	Qty.
NPP CPB 6	450 289	50

Type	Order No	Qty.
NPP/CPB 6	450 299	50

Type	Order No	Qty.
NPP/CPB 6	450 299	50

Comb Connection

Type	Order No	Qty.
UK 9,5/2	480 192	25
UK 9,5/3	480 193	20
UK 9,5/4	480 194	15
UK 9,5/7	480 197	10
UK 9,5/10	480 199	5

Type	Order No	Qty.
UK 13/2	480 202	25
UK 13/3	480 203	20
UK 13/4	480 204	15
UK 13/7	480 207	10
UK 13/10	480 209	5

Type	Order No	Qty.
UK 13/2	480 202	25
UK 13/3	480 203	20
UK 13/4	480 204	15
UK 13/7	480 207	10
UK 13/10	480 209	5

Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix

8/3
1/NA
IP 20
D-NS 5x6, DB 5, DG 6/5

8/3
1/NA
IP 20
D-NS 5x6, DB 5, DG 6/5

8/3
1/NA
IP 20
D-NS 5x6, DB 5, DG 6/5

Package Quantity
50 pcs.

50 pcs.

25 pcs.

25 pcs.
