



CTP 2.5 ET


Width: 5,2 mm



65,00

CTP 2.5 CT

Width: 5,2 mm



85,60

Cat No:

337 050

Voltage, V ~	Current, A	Cross-Section
		2,5 mm ²
		AWG 28-12

Conductor cross section solid (min.-max.)	0,08 - 4 mm ²
Conductor cross section stranded (min.-max.)	0,14 - 2,5 mm ²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve	0,5 mm ²
AWG Conductor	28-12
Insulation Stripping Length (min.-max.)	8-10 mm
Screwdriver	

Diode Reverse Voltage	
Diode Current	
Diode	

Type	Order No	Qty.
NPP/CTP 2,5 ET	451 082 T	50

Cat No:

337 060

Voltage, V ~	Current, A	Cross-Section
		2,5 mm ²
		AWG 28-12

Conductor cross section solid (min.-max.)	0,08 - 4 mm ²
Conductor cross section stranded (min.-max.)	0,14 - 2,5 mm ²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve	0,5 mm ²
AWG Conductor	28-12
Insulation Stripping Length (min.-max.)	8-10 mm
Screwdriver	

Diode Reverse Voltage	
Diode Current	
Diode	

Type	Order No	Qty.
NPP/CTP 2,5 CT	451 092 T	50

End Plate



Type	Order No	Qty.
NPP/CTP 2,5 ET	451 082 T	50

Partition Plate



Type	Order No	Qty.
APP/CTP 2,5E	464 039	50

Type	Order No	Qty.

Test Plug



Type	Order No	Qty.
TF02	493 020	5

Type	Order No	Qty.

Technical Data

Rated Impulse Voltage / Pollution severity	6/3
Insulation material group / Gauge pin code according to IEC 60947-1	1/A3
Protection class / Protection conductor type	IP20/PE
Marking Tags (Dekafix)	
See pages 326-333 for a list of Dekafix	D-NS 5,2x6, SLF-P1 W

Rated Impulse Voltage / Pollution severity	6/3
Insulation material group / Gauge pin code according to IEC 60947-1	1/A3
Protection class / Protection conductor type	IP20/PE
Marking Tags (Dekafix)	
See pages 326-333 for a list of Dekafix	D-NS 5,2x6, SLF-P1 W

Rated Impulse Voltage / Pollution severity	6/3
Insulation material group / Gauge pin code according to IEC 60947-1	1/A3
Protection class / Protection conductor type	IP20/PE
Marking Tags (Dekafix)	
See pages 326-333 for a list of Dekafix	D-NS 5,2x6, SLF-P1 W

Package Quantity

--

50

50
