

2.3 Marking For Cables

2.3.4 Printable Heatshrink Markers - HSL Series

- Flexible
- Zero halogen (HF)
- Flame retardant
- Low smoke generation when it burns
- Continuous Operating Temperature: -45°C to 125°C
- Shrink Temperature: 120°C
- RoHS compliant



Order No	Product	Cross- Section (mm²)	Length (m)	Color	Qty.
579 010	HSL-02-Y	0.25 ~ 1	400	Yellow ●	1
579 011	HSL-03-Y	1 ~ 1.5	400	Yellow ●	1
579 012	HSL-4.5-Y	2.5	200	Yellow ●	1
579 013	HSL-06-Y	4 ~ 6	200	Yellow ●	1
579 014	HSL-10-Y	6 ~ 10	100	Yellow ●	1
579 015	HSL-12-Y	6 ~ 12.7	100	Yellow ●	1
579 016	HSL-15-Y	7.5 ~ 15	100	Yellow ●	1
579 017	HSL-19-Y	9.5 ~ 19	100	Yellow ●	1
579 018	HSL-25-Y	12.5 ~ 25	50	Yellow ●	1
579 019	HSL-28-Y	14 ~ 28	50	Yellow ●	1
579 020	HSL-30-Y	16 ~ 30	50	Yellow ●	1

*HSL Heat shrink tubing is printed with 1020013 coded ribbon.

Order No	Product	Qty.
1020 050	HSL Adapter for TTP Series	1
1020 060	HSL Adapter for TE Series	1
1020 070	HSL Adapter for TX Series	1

2.3.5 Cable Labels (Use With Cable Tie)



Order No	Product	Print Area (mm)	Cable Ø	Cable Tie Hole Size	Color	Qty.
808 473	TTKB 60x10 YL/W	44x10mm	2-10	5x2mm	Yellow/White ●○	500
808 474	TTKB 60x10 RD/W	44x10mm	2-10	5x2mm	Red/White ●○	500
808 475	TTKB 60x10 BL/W	44x10mm	2-10	5x2mm	Blue/White ●○	500
808 476	TTKB 60x10 GN/W	44x10mm	2-10	5x2mm	Green/White ●○	500
808 477	TTKB 60x10 SV/W	44x10mm	2-10	5x2mm	Silver/White ●○	500

* TTKB label is double colored.