


IBKN 4
525 441



IBKN 16
525 451




IBKN 35
525 461



Electrical Ratings			
Cross-Sec.	4 mm²	16 mm²	35 mm²
Insulation Stripping Length (min.-max.)	16 mm	16 mm	16 mm
Fixing Screw	M 4	M 5	M 6
Busbar Dimensions	10 x 3 / 12 x 3	10 x 3 / 12 x 3	10 x 3 / 12 x 3
Isolation Width	Blue	Blue	Blue
Torque	1,5 - 1,8 Nm	2,5 - 3 Nm	3,2 - 3,7 Nm
Qty.			
	50	50	50
Connection Data			
Solid Strand	0,5 ... 6 mm²	1,5 ... 16 mm²	2,5 ... 35 mm²
Fine Strand,	0,5 ... 4 mm²	1,5 ... 16 mm²	2,5 ... 35 mm²
AWG Conductor	20 ... 10	16 ... 6	14 ... 2
Dimensions			
a	18	18	18
b	7	10	14

IBKN 4
525 442T



IBKN 16
525 452T



IBKN 35
525 462T



Electrical Ratings			
Cross-Sec.	4 mm²	16 mm²	35 mm²
Insulation Stripping Length (min.-max.)	16 mm	16 mm	16 mm
Fixing Screw	M 4	M 5	M 6
Busbar Dimensions	10 x 3 / 12 x 3	10 x 3 / 12 x 3	10 x 3 / 12 x 3
Isolation Width	Yellow-Green	Yellow-Green	Yellow-Green
Torque	1,5 - 1,8 Nm	2,5 - 3 Nm	3,2 - 3,7 Nm
Qty.			
	50	50	50
Connection Data			
Solid Strand	0,5 ... 6 mm²	1,5 ... 16 mm²	2,5 ... 35 mm²
Fine Strand,	0,5 ... 4 mm²	1,5 ... 16 mm²	2,5 ... 35 mm²
AWG Conductor	20 ... 10	16 ... 6	14 ... 2
Dimensions			
a	18	18	18
b	7	10	14