



SRD 4 ED-B

Width: 6,2 mm




38,30
MF 35 x 7,5

76,60

SRD 4 ET

Width: 6,2 mm



38,30
MF 35 x 7,5

76,60

Cat No:

311 729

311 720

Voltage, V ~	Current, A	Cross-Section
800	1	4 mm ²
300	1	AWG 28-10
The max. current is determined by the diode. Installed: Diode 1N 4007, reverse voltage: 1300 V, maximum continuous current: 0.5 A.		

0,08 -6 mm ²
0,14 - 4 mm ²
1 mm ²
28-10
8-10
KT3 (0,6x3,5)

1000V
1 A
1 N 4007

Type	Order No	Qty.
NPP/SRD 4E	451 199	50

Type	Order No	Qty.
APP/SRD 4E	464 129	50

Type	Order No	Qty.
TF Ø2	493 020	5

Type	Order No	Qty.
CS 4/2	470 112	25
CS 4/3	470 113	20
CS 4/4	470 114	15
CS 4/5	470 115	10
CS 4/10	470 119	5
CS 4/20	470 180	10

8/3
1/A3
IP20/NA
D-NS 6,2x6, SLF-P1 W

50

Cat No:

337 180

Voltage, V ~	Current, A	Cross-Section
		4 mm ²
		AWG 28-10

0,08 -6 mm ²
0,14 - 4 mm ²
1 mm ²
28-10
8-10
KT3 (0,6x3,5)

Type	Order No	Qty.
NPP/SRD 4E	451 192T	50

Type	Order No	Qty.
APP/SRD 4E	464 129	50

Type	Order No	Qty.
TF Ø2	493 020	5

8/3
1/A3
IP20/PE
D-NS 6,2x6, SLF-P1 W

50
