


MYK Series Mini Terminals

MYKR 2,5

Width: 5 mm




Cat No:

- 306 509
- 306 500

MPK 2,5

Width: 6,2 mm



Cat No:

- 306 519
- 306 510



Electrical Ratings
CE (EN 60947-7-1)
UL
VDE (IEC 60947-7-1)
CSA
ATEX

Connection Data
Conductor cross section solid (min.-max.)
Conductor cross section stranded (min.-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve
AWG Conductor
Insulation Stripping Length (min.-max.)
Screwdriver

End Plate

Push-in Cross Connection

Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix

Package Quantity
50 pcs.

Voltage, V ~	Current, A	Cross-Section
750	24	2,5 mm²

0,08-4 mm²
0,08-2,5 mm²
0,5 mm²
AWG 28-12
9-10 mm
KTD 2 (0,5x3,0)

Type	Order No	Qty.
NPP 1 MYK	446 429	100
NPP 2 MYK	446 439	100

Type	Order No	Qty.
UK 2,5/2	476 222	25
UK 2,5/3	476 223	20
UK 2,5/4	476 224	15
UK 2,5/10	476 229	5
UK 2,5/16	474 260	10
UK 2,5/20	474 200	10

8/3
1/B3
IP 20 / -
DB 5

50 pcs.

Voltage, V ~	Current, A	Cross-Section
500	24	2,5 mm²

0,08-4 mm²
0,08-2,5 mm²
0,5 mm²
AWG 28-12
9-10 mm
KTD 2 (0,5x3,0)

Type	Order No	Qty.
DDR_MPK 2,5	450 459	25

Type	Order No	Qty.

8/3
1/B3
IP 20 / -
DB 5, DG 6/5, D-NS 6,2x6

50 pcs.
