


PRD 10

Coming
Soon...

PRD 10

Width: 10 mm




Cat No:

329 659
329 650

PRD 10T

Width: 10 mm



Cat No:

337 730



Electrical Ratings	Voltage, V ~	Current, A	Cross-Section	Voltage, V ~	Current, A	Cross-Section
IEC (EN 60947-7-1/EN 60947-7-2)	1000	57	10 mm ²			10 mm ²
UL						
VDE (IEC 60947-7-1)						
CSA						
ATEX						
Connection Data	Connection Data			Connection Data		
Conductor cross section solid (min.-max.)	0,2 - 16 mm ²			0,2 - 16 mm ²		
Conductor cross section stranded (min.-max.)	0,2 - 10 mm ²			0,2 - 10 mm ²		
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve	2,5 mm ²			2,5 mm ²		
AWG Conductor	24-6			24-6		
Insulation Stripping Length (min.-max.)	16-18			16-18		
Screwdriver	KT4 (0,8x4,0)			KT4 (0,8x4,0)		
Technical Data For Diode	Technical Data For Diode			Technical Data For Diode		
Diode Reverse Voltage						
Diode Current						
Diod						
End Plate	Type	Order No	Qty.	Type	Order No	Qty.
	NPP/PRD 10	451 509	50	NPP/PRD 10	451 502T	50
Partition Plate	Type	Order No	Qty.	Type	Order No	Qty.
	APP/PRD 10	464 259	50	APP/PRD 10	464 259	50
Test Plug	Type	Order No	Qty.	Type	Order No	Qty.
	TF Ø2,3	493 023	5	TF Ø2,3	493 023	5
Cross Connection	Type	Order No	Qty.	Type	Order No	Qty.
	CS 10/2	470 132	25			
	CS 10/3	470 133	20			
	CS 10/4	470 134	15			
	CS 10/5	470 135	10			
	CS 10/10	470 139	5			
Technical Data	Technical Data			Technical Data		
Rated Impulse Voltage / Pollution severity	8/3			8/3		
Insulation material group / Gauge pin code according to IEC 60947-1	1/A6			1/A6		
Protection class / Protection conductor type	IP20/NA			IP20/PE		
Marking Tags (Dekafix)	Marking Tags (Dekafix)			Marking Tags (Dekafix)		
See pages 326-333 for a list of Dekafix	D-NS 10x10, SLF-P1 W, DG 10/10			D-NS 10x10, SLF-P1 W, DG 10/10		
Package Quantity	Package Quantity			Package Quantity		
	50			50		