


PRD 2,5-3SLD-PNP



Cat No:

328 649
328 640

Voltage, V ~	Current, A	Cross-Section
24	24	2,5 mm²

0,08 - 4 mm²
0,14 - 2,5 mm²
0,5 mm²
28-12
8-10
KT1 (0,4x2,5)

Type	Order No	Qty.
NPP/SRD 2,5-3S	451 179	50


Type	Order No	Qty.
TF Ø2	493 020	5

Type	Order No	Qty.
CS 2,5/2	470 102	25
CS 2,5/3	470 103	20
CS 2,5/4	470 104	15
CS 2,5/5	470 105	10
CS 2,5/10	470 109	5
CS 2,5/20	470 170	10

8/3
1/A3
IP20/NA
D-NS 5,2x6, SLF-P2 W, KCSLF-W 4,9x100mm

50

PRD 2,5-2ST



Cat No:

328 659
328 650

Voltage, V ~	Current, A	Cross-Section
250	24	2,5 mm²

0,08 - 4 mm²
0,14 - 2,5 mm²
0,5 mm²
28-12
8-10
KT1 (0,4x2,5)

Type	Order No	Qty.
NPP/SRD 2,5-3S	451 179	50

Type	Order No	Qty.
TF Ø2	493 020	5

Type	Order No	Qty.
CS 2,5/2	470 102	25
CS 2,5/3	470 103	20
CS 2,5/4	470 104	15
CS 2,5/5	470 105	10
CS 2,5/10	470 109	5
CS 2,5/20	470 170	10

8/3
1/A3
IP20/NA/PE
D-NS 5,2x6, SLF-P2 W, KCSLF-W 4,9x100mm

50
