



PRD 2,5 A

PRD 2,5 AD-A

Width: 5,2 mm




37,30
MR 35 x 7,5

65,40

PRD 2,5 AD-B

Width: 5,2 mm



37,30
MR 35 x 7,5

65,40

Cat No:

328 249
328 240

Cat No:

328 259
328 250



Electrical Ratings

IEC (EN 60947-7-1/EN 60947-7-2)
UL
VDE (IEC 60947-7-1)
CSA
ATEX

Voltage, V ~	Current, A	Cross-Section
500	1	2,5 mm ²
The max. current is determined by the diode. Installed: Diode 1N 4007, reverse voltage: 1300 V, maximum continuous current: 0.5 A.		

Voltage, V ~	Current, A	Cross-Section
500	1	2,5 mm ²
The max. current is determined by the diode. Installed: Diode 1N 4007, reverse voltage: 1300 V, maximum continuous current: 0.5 A.		

Connection Data

Conductor cross section solid (min.-max.)
Conductor cross section stranded (min.-max.)
2 conductors with same cross section, stranded,
TWIN ferrules with plastic sleeve
AWG Conductor
Insulation Stripping Length (min.-max.)
Screwdriver

0,08 - 4 mm ²
0,14 - 2,5 mm ²
0,5 mm ²
28-12
8-10
KT1 (0,4x2,5)

0,08 - 4 mm ²
0,14 - 2,5 mm ²
0,5 mm ²
28-12
8-10
KT1 (0,4x2,5)

Technical Data For Diode

Diode Reverse Voltage
Diode Current
Diod

1000V
1 A
1 N 4007

1000V
1 A
1 N 4007

End Plate



Type	Order No	Qty.
NPP/SRD 2,5E	451 159	50

Type	Order No	Qty.
NPP/SRD 2,5E	451 159	50

Partition Plate



Type	Order No	Qty.
APP/SRD 2,5E	464 079	50

Type	Order No	Qty.
APP/SRD 2,5E	464 079	50

Test Plug



Type	Order No	Qty.
TF Ø2	493 020	5

Type	Order No	Qty.
TF Ø2	493 020	5

Cross Connection



Type	Order No	Qty.
CS 2,5/2	470 102	25
CS 2,5/3	470 103	20
CS 2,5/4	470 104	15
CS 2,5/5	470 105	10
CS 2,5/10	470 109	5
CS 2,5/20	470 170	10

Type	Order No	Qty.
CS 2,5/2	470 102	25
CS 2,5/3	470 103	20
CS 2,5/4	470 104	15
CS 2,5/5	470 105	10
CS 2,5/10	470 109	5
CS 2,5/20	470 170	10

Technical Data

Rated Impulse Voltage / Pollution severity
Insulation material group /
Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type

Marking Tags (Dekafix)

See pages 326-333 for a list of Dekafix

6/3
1/A3
IP20/NA
D-NS 5,2x6, SLF-P1 W

6/3
1/A3
IP20/NA
D-NS 5,2x6, SLF-P1 W

Package Quantity

50

50
