



PRD 2,5 C

PRD 2,5 Cx2

PRD 2,5 CT

Width: 5,2 mm

Width: 5,2 mm



78,10

78,10

37,30
MR 35 x 7,5

37,30
MR 35 x 7,5



Electrical Ratings
IEC (EN 60947-7-1/EN 60947-7-2)
UL
VDE (IEC 60947-7-1)
CSA
ATEX

Connection Data
Conductor cross section solid (min.-max.)
Conductor cross section stranded (min.-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve
AWG Conductor
Insulation Stripping Length (min.-max.)
Screwdriver

Technical Data For Diode
Diode Reverse Voltage
Diode Current
Diod

End Plate

Partition Plate

Test Plug

Cross Connection

Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix

Package Quantity
50

Cat No:

- 328 149
- 328 140

Cat No:

- 337 640

Voltage, V ~	Current, A	Cross-Section
800	24	2,5 mm²

Conductor cross section solid (min.-max.)	0,08 -4 mm²
Conductor cross section stranded (min.-max.)	0,14 - 2,5 mm²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve	0,5 mm²
AWG Conductor	28-12
Insulation Stripping Length (min.-max.)	8-10
Screwdriver	KT1 (0,4x2,5)

Diode Reverse Voltage
Diode Current
Diod

Type	Order No	Qty.
NPP / SRD 2.5C	451 189	50

Type	Order No	Qty.
APP / SRD 2.5C	464 119	50

Type	Order No	Qty.
TF Ø2	493 020	5

Type	Order No	Qty.
CS 2,5/2	470 102	25
CS 2,5/3	470 103	20
CS 2,5/4	470 104	15
CS 2,5/5	470 105	10
CS 2,5/10	470 109	5
CS 2,5/20	470 170	10

Rated Impulse Voltage / Pollution severity	8/3
Insulation material group / Gauge pin code according to IEC 60947-1	1/A3
Protection class / Protection conductor type	IP20/NA
Marking Tags (Dekafix)	D-NS 5,2x6, SLF-P1 W

Package Quantity	50
------------------	----

Voltage, V ~	Current, A	Cross-Section
		2,5 mm²

Conductor cross section solid (min.-max.)	0,08 -4 mm²
Conductor cross section stranded (min.-max.)	0,14 - 2,5 mm²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve	0,5 mm²
AWG Conductor	28-12
Insulation Stripping Length (min.-max.)	8-10
Screwdriver	KT1 (0,4x2,5)

Diode Reverse Voltage
Diode Current
Diod

Type	Order No	Qty.
NPP / SRD 2.5C	451 182T	50

Type	Order No	Qty.
APP / SRD 2.5C	464 119	50

Type	Order No	Qty.
TF Ø2	493 020	5

Type	Order No	Qty.

Rated Impulse Voltage / Pollution severity	8/3
Insulation material group / Gauge pin code according to IEC 60947-1	1/A3
Protection class / Protection conductor type	IP20/PE
Marking Tags (Dekafix)	D-NS 5,2x6, SLF-P1 W

Package Quantity	50
------------------	----