


PRD 2,5

PRD 2,5

Width: 5,2 mm




52,20

37,30
MF 35 x 7,5

PRD 2,5 D-A

Width: 5,2 mm



52,20

37,30
MF 35 x 7,5

Cat No:

328 059RP
328 050RP

Cat No:

328 069
328 060



Electrical Ratings
IEC (EN 60947-7-1/EN 60947-7-2)
UL
VDE (IEC 60947-7-1)
CSA
ATEX

Connection Data
Conductor cross section solid (min.-max.)
Conductor cross section stranded (min.-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve
AWG Conductor
Insulation Stripping Length (min.-max.)
Screwdriver

Technical Data For Diode
Diode Reverse Voltage
Diode Current
Diod

End Plate


Partition Plate


Test Plug


Cross Connection


Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix

Package Quantity
50

Voltage, V ~	Current, A	Cross-Section
800	24	2,5 mm²

Conductor cross section solid (min.-max.)	Conductor cross section stranded (min.-max.)	2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve	AWG Conductor	Insulation Stripping Length (min.-max.)	Screwdriver
0,08 - 4 mm²	0,14 - 2,5 mm²	0,5 mm²	28-12	8-10	KT1 (0,4x2,5)

Diode Reverse Voltage	Diode Current	Diod

Type	Order No	Qty.
NPP / SRD 2.5	451 059	50

Type	Order No	Qty.
APP / SRD 2.5	464 029	50

Type	Order No	Qty.
TF Ø2	493 020	5

Type	Order No	Qty.
CS 2,5/2	470 102	25
CS 2,5/3	470 103	20
CS 2,5/4	470 104	15
CS 2,5/5	470 105	10
CS 2,5/10	470 109	5
CS 2,5/20	470 170	10

Rated Impulse Voltage / Pollution severity	Insulation material group / Gauge pin code according to IEC 60947-1	Protection class / Protection conductor type	Marking Tags (Dekafix)
8/3	1/A3	IP20/NA	D-NS 5,2x6, SLF-P1 W

Package Quantity
50

Voltage, V ~	Current, A	Cross-Section
800	1	2,5 mm²

Conductor cross section solid (min.-max.)	Conductor cross section stranded (min.-max.)	2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve	AWG Conductor	Insulation Stripping Length (min.-max.)	Screwdriver
0,08 - 4 mm²	0,14 - 2,5 mm²	0,5 mm²	28-12	8-10	KT1 (0,4x2,5)

Diode Reverse Voltage	Diode Current	Diod

Type	Order No	Qty.
NPP / SRD 2.5	451 059	50

Type	Order No	Qty.
APP / SRD 2.5	464 029	50

Type	Order No	Qty.
TF Ø2	493 020	5

Type	Order No	Qty.
CS 2,5/2	470 102	25
CS 2,5/3	470 103	20
CS 2,5/4	470 104	15
CS 2,5/5	470 105	10
CS 2,5/10	470 109	5
CS 2,5/20	470 170	10

Rated Impulse Voltage / Pollution severity	Insulation material group / Gauge pin code according to IEC 60947-1	Protection class / Protection conductor type	Marking Tags (Dekafix)
8/3	1/A3	IP20/NA	D-NS 5,2x6, SLF-P1 W

Package Quantity
50