


PRD 4

Coming
Soon...

PRD 4

Width: 6,2 mm




60,10

38,30
MR 35 x 7,5

PRD 4T

Width: 6,2 mm



60,10

38,30
MR 35 x 7,5

Cat No:

329 009
329 000

Cat No:

337 670



Electrical Ratings
IEC (EN 60947-7-1/EN 60947-7-2)
UL
VDE (IEC 60947-7-1)
CSA
ATEX

Voltage, V ~	Current, A	Cross-Section
800	32	4 mm ²

Voltage, V ~	Current, A	Cross-Section
		4 mm ²

Connection Data
Conductor cross section solid (min.-max.)
Conductor cross section stranded (min.-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve
AWG Conductor
Insulation Stripping Length (min.-max.)
Screwdriver

0,08 - 6 mm ²
0,14 - 4 mm ²
1 mm ²
28-10
8-10
KT3 (0,6x3,5)

0,08 - 6 mm ²
0,14 - 4 mm ²
1 mm ²
28-10
8-10
KT3 (0,6x3,5)

Technical Data For Diode
Diode Reverse Voltage
Diode Current
Diod

End Plate


Type	Order No	Qty.
NPP/SRD 4	451 239	50

Type	Order No	Qty.
NPP/SRD 4	451 232T	50

Partition Plate


Type	Order No	Qty.
APP/SRD 4	464 149	50

Type	Order No	Qty.
APP/SRD 4	464 149	50

Test Plug


Type	Order No	Qty.
TF Ø2	493 020	5

Type	Order No	Qty.
TF Ø2	493 020	5

Cross Connection


Type	Order No	Qty.
CS 4/2	470 112	25
CS 4/3	470 113	20
CS 4/4	470 114	15
CS 4/5	470 115	10
CS 4/10	470 119	5
CS 4/20	470 180	10

Type	Order No	Qty.

Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix

8/3
1/A4
IP20/NA
D-NS 6,2x6, SLF-P1 W

8/3
1/A4
IP20/PE
D-NS 6,2x6, SLF-P1 W

Package Quantity

50

50
