


PRD 6

PRD 6

Width: 8 mm



39,45
MF 35 x 7,5


69,30

Cat No:

329 589
329 580

PRD 6T

Width: 8 mm



39,45
MF 35 x 7,5

69,30

Cat No:

337 710



Electrical Ratings
IEC (EN 60947-7-1/EN 60947-7-2)
UL
VDE (IEC 60947-7-1)
CSA
ATEX

Connection Data
Conductor cross section solid (min.-max.)
Conductor cross section stranded (min.-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve
AWG Conductor
Insulation Stripping Length (min.-max.)
Screwdriver

Technical Data For Diode
Diode Reverse Voltage
Diode Current
Diod

End Plate

Partition Plate

Test Plug

Cross Connection

Technical Data
Rated Impulse Voltage / Pollution severity
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Marking Tags (Dekafix)
See pages 326-333 for a list of Dekafix

Package Quantity
50

Voltage, V ~	Current, A	Cross-Section
1000	41	6 mm²

0,2 - 10 mm²
0,2 - 6 mm²
1,5 mm²
24-8
10-12
KT4 (0,8x4,0)

Type	Order No	Qty.
NPP/PRD 6	451 489	50

Type	Order No	Qty.
APP/PRD 6	464 239	50

Type	Order No	Qty.
TF Ø2,3	493 023	5

Type	Order No	Qty.
CS 6/2	470 122	25
CS 6/3	470 123	20
CS 6/4	470 124	15
CS 6/5	470 125	10
CS 6/10	470 129	5

8/3
1/A5
IP20/NA
D-NS 8x10, SLF-P1 W, DG 10/8

50

Voltage, V ~	Current, A	Cross-Section
		6 mm²

0,2 - 10 mm²
0,2 - 6 mm²
1,5 mm²
24-8
10-12
KT4 (0,8x4,0)

Type	Order No	Qty.
NPP/PRD 6	451 482T	50

Type	Order No	Qty.
APP/PRD 6	464 239	50

Type	Order No	Qty.
TF Ø2,3	493 023	5

Type	Order No	Qty.

8/3
1/A5
IP20/PE
D-NS 8x10, SLF-P1 W, DG 10/8

50
