

Terminals Strips


- The product in the figure is the new psk 1/2 terminal strip.
- For allowing marking, label slots are designed according to DB 5 and DG 6/5 Marking Tags (Dekafix)
- Assembly of the terminal should be made with maximum 3 mm Width screw.



PSK 1/2
420 020



PSK 1/12
420 120



PSK 2/2
421 020



PSK 2/10
421 100




Electrical Ratings	Voltage / Current / Cross-Section	Voltage / Current / Cross-Section	Voltage / Current / Cross-Section	Voltage / Current / Cross-Section
TSE (EN 60998-2-1)	400 V ~ / 24 A / 2,5 mm²	400 V ~ / 24 A / 2,5 mm²	660 V ~ / 41 A / 6 mm²	660 V ~ / 41 A / 6 mm²
Insulation Stripping Length (min.-max.)	5 mm	5 mm	9 mm	9 mm
Torque	0,4 - 0,6 Nm	0,4 - 0,6 Nm	0,5 - 0,8 Nm	0,5 - 0,8 Nm
Qty.				
	100	100	100	20
Screwdriver				
	IKT3 (0,6x3,5)			


Junction Box Terminals

- Suitable for 1,5 - 2,5 mm² solid strand cables
- Cage clamp connection
- One-point test
- Disassembling by turning the cable left


BUK 2,5/3
425 235



BUK 2,5/4
425 245



BUK 2,5/5
425 255



BUK 4/3
425 350



Electrical Ratings	Voltage / Current / Cross-Section	Voltage / Current / Cross-Section	Voltage / Current / Cross-Section	Voltage / Current / Cross-Section
IEC 60998-1, IEC 60998-2-1 (VDE)	450 V ~ / 24 A / 2,5 mm²	450 V ~ / 24 A / 2,5 mm²	450 V ~ / 24 A / 2,5 mm²	450 V ~ / 32 A / 4 mm²
Connection Data				
Solid Strand	1,0 - 2,5 mm²	1,0 - 2,5 mm²	1,0 - 2,5 mm²	0,5 - 4 mm²
Insulation Stripping Length (min.-max.)	7 mm	7 mm	7 mm	11 mm
AWG Conductor	22 ... 12	22 ... 12	22 ... 12	22...16
Dimensions				
a	9,4	9,4	9,4	10
b	19,4	19,4	19,4	19,2
c	13,8	17,6	21,1	19,1
Qty.				
	100	100	100	50