

FILTER FAN PLUS - SIZE 2 (124 X 124 MM)

FPI 018



Filter fan FPI size 2 (124 x 124 mm) for air conditioning enclosures and casings. Configuration: FPI - airflow direction "in" (standard version: blowing). Optimum air conditioning of your enclosure: The Filter Fan Plus blows cooler outside air into the enclosure. The warmer air inside the enclosure is discharged via the exit filter. The resulting air flow cools the enclosure and protects the components from overheating.

- Only one filter mat required (on the filter fan)
- Easy installation thanks to mounting frame with twist locks
- Effective air circulation
- Accessories: Hose-proof hood to increase the protection type to IP56



OVERVIEW TECHNICAL DATA

Protection class	I
Protection type	IP54
Material hood	Plastic to UL94 V-0, light gray
Filter material	Plastic fibre with progressive structure
Filter mat	G3
Casing	Plastic to UL94 V-0, light gray
AC/DC	AC
Axial fan	Fan body aluminium, rotor metal
Service life	>37000 h
Operating temperature	-40 °C - 70 °C
Operating humidity	≤90 % RH
Storage humidity	≤90 % RH
Storage temperature	-40 °C - 70 °C
Connection	2 stranded wires, 300 mm
Mounting frame	With 4 built-in rotary latches for locking
Height	152 mm
Width	152 mm
Depth	91 mm
Installation depth	66 mm
Weight	800 g
Mounting cut-out	124 x 124 mm
Note	Other voltages on request;Drilling pattern for screw fixing marked on mounting frame.



Protection type UL

NEMA Type 12

PRODUCT VARIANTS

Article number	Operating voltage	Frequency	Power consumption	Cooling airflow rate outlet filter	Cooling airflow rate blowing	Average emission sound pressure level
01871.9-30	115 V	60 Hz	18 W	51 m³/h	62 m³/h	53 dB(A)
01871.0-30	230 V	50 Hz	19 W	42 m³/h	52 m³/h	49 dB(A)

EXIT FILTER - SIZE 2 (124 X 124 MM)

Article number	Filter mat	Height	Width	Depth	Installation depth	Weight
11871.0-00	ISO coarse 55 % according to ISO 16890 (G3), grav. Initial gravimetric arrestance 57 %	152 mm	152 mm	60 mm	22 mm	200 g

FILTER MAT BAG

Article number	Packaging unit	Filter mat	Mounting cut-out
08634.0-00	5 Piece	ISO coarse 55 % according to ISO 16890 (G3), grav. Initial gravimetric arrestance 57 %	118x118 mm

HOSE-PROOF HOOD

Article number	Material sealing	Cut-out dimensions	Height	Width	Depth	Weight
08671.0-00	Silicone, food safe	FPI/FPO 018 124 x 124 mm	279 mm	225 mm	58 mm	1200 g

TECHNICAL DRAWINGS

