



Protection type UL

NEMA Type 12

PRODUCT VARIANTS

Article number	Operating voltage	Frequency	Cooling airflow rate outlet filter	Cooling airflow rate blowing	Average emission sound pressure level
01880.0-00	230 V	50 Hz	15 m³/h	24 m³/h	38 dB(A)
01880.9-00	115 V	60 Hz	19 m³/h	32 m³/h	41 dB(A)

FILTER MAT BAG

Article number	Packaging unit	Filter mat	Mounting cut-out
08633.0-00	5 Piece	ISO coarse 55 % according to ISO 16890 (G3), grav. Initial gravimetric arrestance 57 %	84x84 mm

HOSE-PROOF HOOD

Article number	Material sealing	Cut-out dimensions	Height	Width	Depth	Weight
08670.0-00	Silicone, food safe	FPI/FPO 018 92 x 92 mm	214 mm	195 mm	48 mm	800 g



Protection type UL

NEMA Type 12

PRODUCT VARIANTS

Article number	Operating voltage	Frequency	Power consumption	Cooling airflow rate outlet filter	Cooling airflow rate blowing	Average emission sound pressure level
01870.9-30	115 V	60 Hz	11 W	16 m³/h	23 m³/h	43 dB(A)
01870.0-30	230 V	50 Hz	12 W	13 m³/h	19 m³/h	39 dB(A)

EXIT FILTER - SIZE 1 (92 X 92 MM)

Article number	Filter mat	Height	Width	Depth	Installation depth	Weight
11870.0-00	ISO coarse 55 % according to ISO 16890 (G3), grav. Initial gravimetric arrestance 57 %	120 mm	120 mm	51 mm	22 mm	200 g

FILTER MAT BAG

Article number	Packaging unit	Filter mat	Mounting cut-out
08633.0-00	5 Piece	ISO coarse 55 % according to ISO 16890 (G3), grav. Initial gravimetric arrestance 57 %	84x84 mm

HOSE-PROOF HOOD

Article number	Material sealing	Cut-out dimensions	Height	Width	Depth	Weight
08670.0-00	Silicone, food safe	FPI/FPO 018 92 x 92 mm	214 mm	195 mm	48 mm	800 g

TECHNICAL DRAWINGS

