

Protection type UL	NEMA Type 12
--------------------	--------------

PRODUCT VARIANTS

Article number	Operating voltage	Frequency	Power consumption	Cooling airflow rate outlet filter	Cooling airflow rate blowing	Average emission sound pressure level
01883.9-00	115 V	60 Hz	81 W	310 m³/h	581 m³/h	68 dB(A)
01883.0-00	230 V	50 Hz	64 W	281 m³/h	536 m³/h	65 dB(A)

FILTER MAT BAG

Article number	Packaging unit	Filter mat	Mounting cut-out
08636.0-00	5 Piece	ISO coarse 55 % according to ISO 16890 (G3), grav. Initial gravimetric arrestance 57 %	215x215 mm

HOSE-PROOF HOOD

Article number	Material sealing	Cut-out dimensions	Height	Width	Depth	Weight
08673.0-00	Silicone, food safe	FPI/FPO 018 223 x 223 mm	415 mm	369 mm	78 mm	2800 g



Protection type UL	NEMA Type 12
--------------------	--------------

PRODUCT VARIANTS

Article number	Operating voltage	Frequency	Power consumption	Cooling airflow rate outlet filter	Cooling airflow rate blowing	Average emission sound pressure level
01873.9-30	115 V	60 Hz	81 W	293 m³/h	332 m³/h	67 dB(A)
01873.0-30	230 V	50 Hz	64 W	271 m³/h	305 m³/h	64 dB(A)

EXIT FILTER - SIZE 4 (223 X 223 MM)

Article number	Filter mat	Height	Width	Depth	Installation depth	Weight
11873.0-00	ISO coarse 55 % according to ISO 16890 (G3), grav. Initial gravimetric arrestance 57 %	257 mm	257 mm	72 mm	25 mm	500 g

FILTER MAT BAG

Article number	Packaging unit	Filter mat	Mounting cut-out
08636.0-00	5 Piece	ISO coarse 55 % according to ISO 16890 (G3), grav. Initial gravimetric arrestance 57 %	215x215 mm

HOSE-PROOF HOOD

Article number	Material sealing	Cut-out dimensions	Height	Width	Depth	Weight
08673.0-00	Silicone, food safe	FPI/FPO 018 223 x 223 mm	415 mm	369 mm	78 mm	2800 g

TECHNICAL DRAWINGS

