



PRODUCT VARIANTS

Article number	Operating voltage	Frequency	Power consumption	Cooling airflow rate outlet filter	Cooling airflow rate blowing	Average emission sound pressure level	Service life	Operating temperature	Weight
01884.9-00	115 V	60 Hz	90 W	391 m³/h	703 m³/h	62 dB(A)	>76000 h	-40 °C - 55 °C	3200 g
01884.0-01	230 V	50 Hz	140 W	599 m³/h	1010 m³/h	70 dB(A)	>54000 h	-40 °C - 55 °C	3400 g
01884.0-00	230 V	50 Hz	95 W	413 m³/h	727 m³/h	63 dB(A)	>76000 h	-40 °C - 55 °C	3200 g
01884.9-01	115 V	60 Hz	165 W	609 m³/h	1031 m³/h	71 dB(A)	>54000 h	50 Hz: —40 - +55 °C 60 Hz: -25 - +50 °C °C	3400 g

FILTER MAT BAG

Article number	Packaging unit	Filter mat	Mounting cut-out
08637.0-00	5 Piece	ISO coarse 55 % according to ISO 16890 (G3), grav. Initial gravimetric arrestance 57 %	283x283 mm

HOSE-PROOF HOOD

Article number	Material sealing	Cut-out dimensions	Height	Width	Depth	Weight
08674.0-00	Silicone, food safe	FPI/FPO 018 291 x 291 mm	485 mm	409 mm	103 mm	3700 g



PRODUCT VARIANTS

Article number	Operating voltage	Frequency	Power consumption	Cooling airflow rate outlet filter	Cooling airflow rate blowing	Average emission sound pressure level	Service life	Operating temperature	Weight	Note
01874.0-30	230 V	50 Hz	95 W	373 m³/h	433 m³/h	62 dB(A)	>76000 h	-25 °C - 55 °C	3100 g	Other voltages on request;Drilling pattern for screw fixing marked on mounting frame.
01874.9-31	115 V	60 Hz	165 W	593 m³/h	665 m³/h	72 dB(A)	>76000 h	-25 °C - 50 °C	3300 g	Drilling pattern for screw fixing marked on mounting frame.
01874.9-30	115 V	60 Hz	90 W	339 m³/h	394 m³/h	61 dB(A)	>76000 h	-25 °C - 35 °C	3100 g	Drilling pattern for screw fixing marked on mounting frame.
01874.0-31	230 V	50 Hz	140 W	560 m³/h	624 m³/h	70 dB(A)	>54000 h	-25 °C - 55 °C	3300 g	Other voltages on request;Drilling pattern for screw fixing marked on mounting frame.

EXIT FILTER - SIZE 5 (291 X 291 MM)

Article number	Filter mat	Height	Width	Depth	Installation depth	Weight
11874.0-00	ISO coarse 55 % according to ISO 16890 (G3), grav. Initial gravimetric arrestance 57 %	322 mm	322 mm	79 mm	25 mm	800 g

FILTER MAT BAG

Article number	Packaging unit	Filter mat	Mounting cut-out
08637.0-00	5 Piece	ISO coarse 55 % according to ISO 16890 (G3), grav. Initial gravimetric arrestance 57 %	283x283 mm

HOSE-PROOF HOOD

Article number	Material sealing	Cut-out dimensions	Height	Width	Depth	Weight
08674.0-00	Silicone, food safe	FPI/FPO 018 291 x 291 mm	485 mm	409 mm	103 mm	3700 g

TECHNICAL DRAWINGS

