

ENCLOSURE HEATER WITHOUT FAN

HV 031



The space-saving fan heater for temperature control in enclosures, casings and technical installation spaces provides contactor protection against condensation. Resistance heater available in five power levels, each in AC 230 V and AC 120 V. HV 031 enclosure heaters are supplied without a fan. The installation of a fan is essential for operation.

- Compact, flat construction
- Overheating protection with automatic shutdown
- Fan self-mounting mandatory
- Clip fixing for 35 mm DIN rail



OVERVIEW TECHNICAL DATA

Temperature monitoring	Overheating protection in the event of fan failure with automatic reset
Protection class	I
Protection type	IP20
Connection case	Plastic to UL94 V-0, black
Heating element	High-performance heating cartridge
Heater element	Aluminium die casting
AC/DC	AC
Frequency	50;60 Hz
Operating temperature	-45 °C - 70 °C
Operating humidity	≤90 % RH
Storage humidity	≤90 % RH
Storage temperature	-45 °C - 70 °C
Connection type	Connection terminal
Torque	0,8 Nm max.
Mounting	Clip for 35 mm DIN rail
Installation position	Airflow direction "in" vertical / connection at the bottom
Height	22 mm
Note	Heating without fan;Heating may only be operated in conjunction with a fan;Heating may only be operated in conjunction with a fan (min. 150 m³/h). There is a risk of overheating!

PRODUCT VARIANTS

Article number	Operating voltage	Heating capacity	Connection	Width	Depth	Weight
03111.0-00	230 V	300 W	3-pole clamp 2.5 mm² max.	119 mm	151 mm	500 g
03100.0-00	230 V	100 W	3-pole clamp 2.5 mm²	80 mm	112 mm	400 g
03110.0-00	230 V	200 W	3-pole clamp 2.5 mm² max.	119 mm	151 mm	500 g
03100.9-00	120 V	100 W	3-pole clamp 2.5 mm² max.	80 mm	112 mm	400 g
03111.9-00	120 V	300 W	3-pole clamp 2.5 mm² max.	119 mm	151 mm	500 g
03112.9-00	120 V	400 W	3-pole clamp 2.5 mm² max.	119 mm	151 mm	500 g
03110.9-00	120 V	200 W	3-pole clamp 2.5 mm² max.	119 mm	151 mm	500 g
03101.0-00	230 V	150 W	3-pole clamp 2.5 mm² max.	80 mm	112 mm	400 g
03101.9-00	120 V	150 W	3-pole clamp 2.5 mm² max.	80 mm	112 mm	400 g
03112.0-00	230 V	400 W	3-pole clamp 2.5 mm² max.	119 mm	151 mm	500 g

TECHNICAL DRAWINGS

