

NEW: LED ENCLOSURE LAMP

SL 025



The flat LED light SL 025 with on/off switch and motion detector is ideal for use in cabinets and casings with electrical/electronic components with a high component density. It can be mounted narrow-sided or wide-sided with screws, or with magnet fixing at any desired position in steel cabinets without installation effort. Thanks to its integrated socket, the SL025 enables the operation of additional electrical devices. The integrated motion detector also replaces a door switch.

- Flat casing
- Wide voltage range
- Light with socket
- Screw and magnet fixing
- LED light element
- Switch and motion detector in one device
- Can be used worldwide certified



OVERVIEW TECHNICAL DATA

Switch	On/off switch and motion detector
Illuminant	LED
Protection class	I
Protection type	IP20
Casing	Plastic to UL94 V-0, light gray
AC/DC	AC
Frequency	50;60 Hz
Power consumption	4 W
Luminous colour	6000 - 7000 K
Luminous flux	560 Lm
Service life	>60000 h
Operating temperature	-40 °C - 60 °C
Operating humidity	≤90 % RH
Storage humidity	≤90 % RH
Storage temperature	-40 °C - 85 °C
Torque	0,8 Nm max.
Connection	Clamp 2.5 mm² with strain relief
Mounting	Screw / magnet
Installation position	any
Height	91 mm
Width	40 mm

Depth	345 mm
Weight	385 g
Note	The socket is operated with mains voltage connected; motion detector has approx. 5 min. fixed duty cycle; motion detector cannot detect movement through glass doors.

PRODUCT VARIANTS

Article number	Socket	Operating voltage	Operating socket	Nominal current socket	CCC
02535.1-00	IT	100 V - 240 V	250 V	16 A	
02530.1-00	DE/RU	100 V - 240 V	250 V	16 A	
02534.1-00	USA	100 V - 120 V	125 V	15 A	
02536.1-00	AU	100 V - 240 V	240 V	10 A	CQC
02532.1-00	CH	100 V - 240 V	250 V	10 A	
02533.1-00	GB/IRE	100 V - 240 V	250 V	13 A	
02531.1-00	FR	100 V - 240 V	250 V	16 A	

TECHNICAL DRAWINGS

